

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

CLAIMS

What is claimed is:

sub
ay

106080-EE52660

1. A communication device adapted for use in an automated monitoring system for providing remote monitoring of electricity consumption, the automated monitoring system comprising a site controller in communication with a plurality of electric meters via a wireless communication network and in communication with a host computer via a wide area network, the communication device comprising:

a data interface configured to receive data related to the electricity consumption of an electric meter;

memory comprising a unique identifier corresponding to the electric meter;

logic configured to receive the data related to the electricity consumption of the electric meter, retrieve the unique identifier corresponding to the electric meter, and generate a transmit message using a predefined communication protocol being implemented by the wireless communication network, the transmit message comprising the unique identifier and the data related to the electricity consumption of the electric meter and configured such that the transmit message may be received by the site controller via the wireless communication network and such that the site controller may identify the electric meter and notify the host computer of the transmit message; and

a wireless transceiver configured for communication over the wireless communication network and configured to provide the transmit signal to the wireless communication network and receive messages from the wireless communication network.

2. The device of claim 1, wherein the logic is stored in memory and the device further comprises a microcontroller configured to implement the logic.

3. The device of claim 1, wherein the wireless transmitter is configured to provide the transmit signal as a radio frequency signal.

1 4. The device of claim 1, wherein the wireless transmitter is configured to provide
2 the transmit signal as a low power radio frequency signal.

1 5. The device of claim 1, wherein the data interface is adapted for use with an
2 electromechanical electric meter which measures the electricity consumption associated
3 with the electric meter via a meter wheel and the received data related to the electricity
4 consumption of the electric meter corresponds to a number of rotations of the meter
5 wheel.

1 6. The device of claim 1, wherein the predefined communication protocol
2 comprises a data packet comprising:

- 3 a receiver address identifying the receiver of the data packet;
- 4 a sender address identifying the sender of the data packet; and
- 5 a command indicator specifying a predefined command code;

1 7. The device of claim 6, wherein the data packet further comprises a data payload
2 and a checksum field for performing a redundancy check.

1 8. The device of claim 7, wherein the data packet further comprises:
2 a packet length indicator which indicates a total number of bytes in the
3 current packet;
4 a total packet indicator which indicates the total number of packets in the
5 current message; and
6 a current packet indicator which identifies the current packet; and
7 a message number identifying the current message.

12. The device of claim 9, wherein the wireless transmitter is configured to provide the transmit signal as a low power radio frequency signal.

1 13. The device of claim 9, wherein the electric meter measures the electricity
2 consumption associated with the electric meter via an electromagnetic meter wheel and
3 the received data related to the electricity consumption of the electric meter
4 corresponds to a number of rotations of the meter wheel.

1 14. The device of claim 9, wherein the predefined communication protocol
2 comprises a data packet comprising:
3 a receiver address identifying the receiver of the data packet;
4 a sender address identifying the sender of the data packet; and
5 a command indicator specifying a predefined command code;

1 15. The device of claim 14, wherein the data packet further comprises a data
2 payload and a checksum field for performing a redundancy check.

1 16. The device of claim 15, wherein the data packet further comprises:
2 a packet length indicator which indicates a total number of bytes in the
3 current packet;
4 a total packet indicator which indicates the total number of packets in the
5 current message; and
6 a current packet indicator which identifies the current packet; and
7 a message number identifying the current message.

Sub
A
cont. id

09925393-080901

- 1 17. A communication device adapted for use in an automated monitoring system for
2 providing remote monitoring of electricity consumption, the automated monitoring
3 system comprising a site controller in communication with a plurality of electric meters
4 via a wireless communication network and in communication with a host computer via
5 a wide area network, the communication device comprising:
6 a means for receiving data related to the electricity consumption of an electric
7 meter;
8 a means for storing a unique identifier corresponding to the electric meter;
9 a means for receiving the data related to the electricity consumption of the
10 electric meter, retrieving the unique identifier corresponding to the electric meter, and
11 generating a transmit message using a predefined communication protocol being
12 implemented by the wireless communication network, the transmit message comprising
13 the unique identifier and the data related to the electricity consumption of the electric
14 meter and configured such that the transmit message may be received by the site
15 controller via the wireless communication network and such that the site controller may
16 identify the electric meter and notify the host computer of the transmit message; and
17 a means for transmitting the transmit signal to the wireless communication
18 network.
- 1 18. The device of claim 17, further comprising a means for receiving command
2 messages from the wireless communication network.
- 1 19. The device of claim 17, wherein the means for receiving data related to the
2 electricity consumption of the electric meter is adapted for use with an electric meter
3 which measures the electricity consumption via an electromagnetic means.
- 1 20. The device of claim 17, wherein the predefined communication protocol
2 comprises a data packet comprising:
3 a means for identifying the receiver of the data packet;
4 a means for identifying the sender of the data packet; and
5 a command means for specifying a predefined command code;

T.06030" E5E2660

1 a wireless transceiver configured for communication over the wireless
2 communication network and configured to provide the transmit signal to the wireless
3 communication network and receive messages from the wireless communication
4 network.

29

24. The device of claim 22, wherein the predefined communication protocol comprises a data packet comprising:

- a means for identifying the receiver of the data packet;
- a means for identifying the sender of the data packet; and
- a command means for specifying a predefined command code;

25. The device of claim 24, wherein the data packet further comprises:

- a means for indicating a total number of bytes in the current packet;
- a means for indicating the total number of packets in the current message; and
- a means for identifying the current packet; and
- a means for identifying the current message.

26. A system for providing remote monitoring of electricity consumption, the system comprising:

a plurality of electric meters, each of the plurality of electric meters configured to measure the electricity consumption of a load attached to the electric meter;

a plurality of communication devices having a unique address and defining a wireless communication network, each of the plurality of communication devices associated with one of the plurality of electric meters and configured to receive data related to the electricity consumption of the electric meter data and generate a transmit message using a predefined communication protocol being implemented by the wireless communication network, the transmit message comprising the unique identifier and the data related to the electricity consumption of the electric meter; and

a site controller configured for communication with the wireless communication network and configured to receive the transmit message from one of the plurality of communication devices, identify the electric meter associated with the transmit message, and provide information related to the transmit message to a wide area network for delivery to a host computer.

27. The system of claim 26, wherein the site controller is further configured to provide a command message to one of the plurality of communication devices and, in response, the one of the plurality of communication devices provides the transmit message corresponding to the command message.

Set
all
cont'd

0905393-080901

- 1 28. The system of claim 26, further comprising the host computer.
- 1 29. The system of claim 27, wherein the command message is provided to the site
2 controller by the host computer.
- 1 30. The system of claim 27, wherein the host computer is configured to enable a
2 user associated with one of the plurality of electric meters to initiate the command
3 message via the wide area network.
- 1 31. The device of claim 26, wherein the predefined communication protocol
2 comprises a data packet comprising:
3 a receiver address identifying the receiver of the data packet;
4 a sender address identifying the sender of the data packet; and
5 a command indicator specifying a predefined command code;
- 1 32. The device of claim 31, wherein the data packet further comprises a data
2 payload and a checksum field for performing a redundancy check.
- 1 33. The device of claim 32, wherein the data packet further comprises:
2 a packet length indicator which indicates a total number of bytes in the
3 current packet;
4 a total packet indicator which indicates the total number of packets in the
5 current message; and
6 a current packet indicator which identifies the current packet; and
7 a message number identifying the current message.

5/16
24
concord

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16

34. A system for providing remote monitoring of electricity consumption, the system comprising:

a plurality of means for measuring the electricity consumption of an attached load;

a plurality of communication means having a unique address and defining a wireless communication network, each of the plurality of communication means associated with one of the plurality of means for measuring the electricity consumption comprising a means for receiving data related to the electricity consumption of the electric meter data and a means for generating a transmit message using a predefined communication protocol being implemented by the wireless communication network, the transmit message comprising the unique identifier and the data related to the electricity consumption of the electric meter; and

a means for receiving the transmit message from one of the plurality of communication devices, identifying the electric meter associated with the transmit message, and providing information related to the transmit message to a wide area network for delivery to a host computer.

106020-8852660